



Conductor: [26AWG(0.16/7)Bare Copper]x8C  
 Insulation: [PP6331 ID:0.95±0.03]x8C  
 Jacket: PVC NOUL 65P

P1	P2
1 WHITE	8
2 ORANGE	7
3 BLACK	6
4 RED	5
5 GREEN	4
6 YELLOW	3
7 BLUE	2
8 BROWN	1



**Note:**  
 • Material: Housing-polycarbonate, clear  
 Terminal-0.36[.014] thick phosphor bronze.  
 Thick gold in localized gold plate.  
 Area, Gold Flash over the remainder.  
 Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-8/8/S-5	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-8/8/S-7	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-8/8/S-10	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-8/8/S-12	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-8/8/S-14	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-8/8/S-25	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-8/8/S-50	G	15,250±150(50ft)	Silver	15,250-15,260mm



Scale	Free
TOLERANCE	
X.	±X
X.X	±X
X.XX	±X
DIM	TOL
X.°	±X°
X.X°	±X°
Angle	TOL

Id.	Modification	Date	Name

Date: 08.07.13  
 Name: Wilson  
 Drawn: 08.07.13  
 Name: Groll  
 Approved: 08.07.13  
**ASSMANN**  
 WSW components  
 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
 Toll Free: 1-877-277-6266 • Email: info@assmann.us

Title
Modular cable - Straight 8P8C 50µ", 26AWG, Silver, 5-50 feet
ASSMANN WSW-No. AT-S-26-8/8/S-xx
Drawing-No.
Replace
rev00
Sheet 1/1

Unit: mm