

## **Specification Sheet**

Part Number: 596-73834

Thermal Transfer Labels, High-Bond Adhesive, 3.0" x 1.0", Polyester, White, 3000/roll

Article Number	596-73834
Туре	PCP3X1
Color	White (WH)
Features & Benefits	•White polyester is glossy, allowing for the highest resolution and print contrast. •The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term. •The printable surface is highly resistant to chemicals and solvents and can withstand long-term UV exposure.
Quantity Per	roll
Product Description	For the ultimate in chemical and solvent resistance and long term outdoor

durability, the 840 white polyester offers the most aggressive performance features of any other polyester label material. With an initial outdoor life of 7 years, the labels have been tested far beyond the published limits and the acrylic adhesive bonds well to powder coat painted surfaces as well as baked enamel and slightly textured substrates.

Short Description	Thermal Transfer Labels, High-Bond Adhesive, 3.0" x 1.0", Polyester, White, 3000/roll
Global Part Name	PCP3X1-840W-WH
Width W (Imperial)	3.0
Width W (Metric)	76.2
Thickness T (Metric)	64.0
Height H (Imperial)	1.0
Height H (Metric)	25.4
Width of Liner (Metric)	81.28
Width of Liner (imperial)	3.2
Material	Type 840W, Polyester (PET), White (WH)
Material Shortcut	840W
Adhesive	High Bond Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +300°F (-40°C to +149°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	CSA 66956
UL Recognized (US)	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.68
Weight (Imperial)	1.48

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $<sup>\</sup>hbox{@ 2018 HellermannTyton. All rights reserved.}$