

Product Overview

NCV890100: Automotive Switching Regulator, Buck, 1.2 A, 2 MHz

For complete documentation, see the data sheet

The NCV890100 is a fixed-frequency, monolithic, Buck switching regulator intended for Automotive, battery-connected applications that must operate with up to a 36V input supply. The regulator is suitable for systems with low noise and small form factor requirements often encountered in automotive driver information systems. The NCV890100 is capable of converting the typical 4.5 V to 18 V automotive input voltage range to outputs as low as 3.3 V at a constant switching frequency above the sensitive AM band, eliminating the need for costly filters and EMI countermeasures.

The NCV890100 also provides several protection features expected in Automotive power supply systems such as current limit, short-circuit protection and thermal shutdown. In addition, the high switching frequency produces low output voltage ripple even when using small inductor values and an all-ceramic output filter capacitor - forming a space-efficient switching regulator solution.

Features

- · 2-MHz Free-Running Switching Frequency
- Internal N-Channel Power Switch
- Low V_{IN} Operation Down to 4.5 V
- High V_{IN} Operation Up to 36 V
- Withstands Load Dumps to 40 V
- · Logic level Enable Input Can be Directly Tied to Battery
- 1.4 A (min) Cycle-by-Cycle Peak Current Limit
- Short-Circuit Protection enhanced by Frequency Foldback
- ±1.75% Output Voltage Tolerance
- Output Voltage Adjustable Down to 0.8 V
 For more features, see the data sheet

Benefits

Enables the use of small size, low cost inductor and EMC filter

Applications


- Audio
- Infotainment
- · Safety Vision Systems
- Dashboards

End Products

Automotive

Part Electrical Specifications											
Product	Compliance	Status	Topology	Control Mode	V _{CC} Min	V _{CC} Max (V)	V _O Typ (V)	I _O Typ (A)	Efficiency (%)	f _{SW} Typ (kHz)	Package Type
NCV890100MWTXG	AEC Qualified PPAP Capable Pb-free	Active	Step- Down		4.5	40	Adjustable	1.2		2250	DFN-8
NCV890100PDR2G	AEC Qualified PPAP Capable Pb-free	Active	Step- Down		4.5	40	Adjustable	1.2		2250	SOIC-8 EP

Application Diagram



For more information please contact your local sales support at www.onsemi.com Created on: 4/29/2017