

RM Cores (6295230121)



Part Number: 6295230121

95 RM CORE SET

RM (Rectangular Modulus) cores allow better shielding than E type geometries while also providing easier winding accessibility and better power dissipation than a pot core configuration. Fair- Rite \(\sigma \) standard RM cores all have a solid center post and standard height, low profile and alternate materials are available upon request.

 \square RM cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 13 (g)

Dim	mm	mm tol	nominal inch	inch misc.	
	_			men mise.	
A	22.75	± 0.45	0.896	_	
В	8.2	± 0.10	0.323	_	
C	10.8	± 0.20	0.425	_	$\begin{array}{c} \textbf{Chart Legend} \\ \hline \Sigma I / A : Core Constant, & l_e : Effective Path \\ \hline Length, & A_e : Effective Cross- Sectional Area, & V_e \\ \hline Effective Core Volume \\ \hline A_L : Inductance Factor \\ \hline \end{array}$
D	5.5	± 0.15	0.217		
Е	17.3	± 0.30	0.681	_	
F	8.4	± 0.15	0.331	_	
G	9.8	min	0.386	min	
J	19.1	± 0.40	0.752	_	
& 4 =	materia	l grade			Explanation of Part Numbers: Digits 1 & 2 = product class and

Electrical Properties				
$A_L(nH)$	$3500 \pm 25\%$			
Ae(cm ²)	0.6			
$\Sigma l/A(cm^{-1})$	6.7			
l _e (cm)	4.03			
$V_e(cm^3)$	2.419			
$A_{\min}(cm^2)$	0.554			

A_L value is measured at 1 kHz, B < 10 gauss.

888-324-7748

Fair- Rite Products Corp.

One Commercial Row, Wallkill, New York 12589-0288

845-895-2055

Fax: 845-895-2629

ferrites@fair- rite.com

www.fair- rite.com